



INTERNATIONAL® 3300

Product Specifications

Model Configurations	3300	Standard	Maximum
		Front GAW	8,000 lbs
		Rear GAW	17,500 lbs
		Total GVW	25,500 lbs
			10,000 lbs
			23,000 lbs
			33,000 lbs

Wheelbase (in.)	Chassis Weights (lbs)			Dimensions (in.)				Turning Radius	
	Front	Rear	Total	Back of Cab to Rear Axle	Back of Cab to End of Frame	Center of Rear Axle to End of Frame	Over All Length	To Curb	Bumper Clearance
158	4077	3462	7539	---	---	90	274.8	21ft. 6in.	22ft. 9in.
169	4101	3463	7564	---	---	106	308.8	23ft. 8in.	24ft. 11in.
193	4119	3588	7707	---	---	106	331.8	26ft. 6in.	27ft. 8in.
217	4144	3661	7805	---	---	112	362.8	29ft. 6in.	30ft. 9in.
236	4178	3741	7919	---	---	118	386.8	31ft. 8in.	32ft. 11in.
254	4182	3836	8018	---	---	130	416.8	33ft. 11in.	35ft. 1in.
276	4215	3876	8091	---	---	136	444.8	36ft. 7in.	37ft. 9in.

Frame Rails	50,000 PSI	10.125"
--------------------	------------	---------

Front Axle	International	10,000 lb Capacity
	Dana Spicer	8,000 lb Capacity

Front Suspension	Parabolic Taper Leaf w/ Shocks	8,000; 10,000 lb Capacity
-------------------------	--------------------------------	---------------------------

Brakes	Air
	Hydraulic Disc

Steering	Ross
-----------------	------

Exhaust System	Single, Frame Mounted Horizontal Muffler Right or Left Side w/ Horizontal Tail Pipe
-----------------------	---

Electrical System	Leece-Neville	130, 145, 160, 175, 270 Amp Alternators
	Delco-Remy America Inc.	130, 145 Amp Alternators
	International	1100, 1150, 1300, 1950, 2300 CCA Battery System
	Delphi	2100 CCA Battery System
	Long Life Halogen Headlights	



INTERNATIONAL® 3300

Product Specifications

Front End	Tilting Fiberglass Hood	
Paint	Base Coat / Clear Coat, TSA (Acrylic)	
Clutch	Eaton Fuller	
Engine & Equipment	International VT365	175 HP/460 lb-ft to 200 HP/520 lb-ft
	International DT466 High Torque	225 HP/620 lb-ft, 245 HP/660 lb-ft
	International DT466 Standard Torque	210 HP/520 lb-ft to 255 HP/660 lb-ft
	Air Cleaner	Heavy Duty Dual Element w/ Restriction Gauge
Transmissions	TTC	7 Speed Manual
	International	7 Speed Manual
	Spicer	5 Speed Manual
	Allison	5 Speed Automatic; 2000, MD-3060 Series
Rear Axle (Single)	International	13,500; 15,500; 17,500 lb Capacity
	Dana Spicer	17,500; 19,000; 19,800; 21,000; 23,000 lb Capacity
Rear Suspension (Single)	International Air Suspension	12,000; 20,000; 23,000 lb Capacity w/ 9.5" Ride Height
	Spring Suspension	13,500; 15,500; 18,500; 19,800; 20,000; 23,500 lb Capacity Vari-Rate
Fuel Tank	35 – 100 U.S. Gallons Total Capacity	Mounted Between the Rails, Right or Left Side
Cab	None	
Interior Trim	None	
Mirrors	None	
Driver Seats	None	
Passenger Seats	None	



INTERNATIONAL® 3300

Product Specifications

Front Wheels	Painted Steel	19.5", 22.5"; 8, 10 Stud
Rear Wheels	Painted Steel	19.5", 22.5"; 8, 10 Stud
Tires	Goodyear, Michelin	