



INTERNATIONAL® 1652

Product Specifications

Model Configurations	1652 SC 4x2	Standard	Maximum
	Front GAW	6,000 lbs	8,000 lbs
	Rear GAW	15,500 lbs	19,000 lbs
	Total GVW	21,500 lbs	27,000 lbs

Wheelbase (in.)	Chassis Weights (lbs)			Dimensions (in.)				Turning Radius	
	Front	Rear	Total	Back of Cab to Rear Axle	Back of Cab to End of Frame	Center of Rear Axle to End of Frame	Over All Length	To Curb	Bumper Clearance
152	3624	2675	6299	---	---	90	275	23ft. 0in.	24ft. 2in.
170	3698	2708	6406	---	---	106	309	25ft. 4in.	26ft. 7in.
176	3729	2690	6419	---	---	106	315	26ft. 1in.	27ft. 4in.
193	3824	2660	6484	---	---	106	332	28ft. 4in.	29ft. 7in.
218	3943	2620	6563	---	---	112	363	31ft. 7in.	32ft. 10in.
254	4151	2487	6638	---	---	97	383	36ft. 3in.	37ft. 6in.

Frame Rails	80,000 PSI	9.125"
Front Axle	International	9,000 lb Capacity
	Spicer	6,000; 8,000 lb Capacity
Front Suspension	Parabolic Taper Leaf w/ Shocks	8,000 lb Capacity
	Multileaf, Shackle Type w/ Shocks	9,000 lb Capacity
Brakes	Hydraulic Disc	
Steering	Ross	
Exhaust System	Single, Horizontal Muffler and Long Tail Pipe, Frame Mounted Right or Left Side	
Electrical System	Leece-Neville	100 Amp Alternator
	Delco-Remy America Inc.	200 Amp Alternator
	International	1100, 1300 CCA Battery System
Front End	None	
Paint	None	



INTERNATIONAL® 1652

Product Specifications

Clutch	Eaton Fuller	
Engine & Equipment	International VT365	175 HP/460 lb-ft to 200 HP/520 lb-ft
Transmissions	Spicer	5 Speed Manual
	Allison	5 Speed Automatic
Rear Axle (Single)	International	13,500; 15,500 lb Capacity
	Dana Spicer	17,500; 19,000 lb Capacity
Rear Suspension (Single)	Steel Spring Suspension	13,500; 15,500; 18,500; 20,000 lb Capacity Vari- Rate
Fuel Tank	35 or 65 U.S. Gallons Total Capacity	Mounted Right or Left Side
Cab	PLATFORM Standard Location	
Interior Trim	None	
Mirrors	None	
Driver Seats	None	
Passenger Seats	None	
Front Wheels	Painted Steel	19.5", 22.5"; 8,10 Stud
Rear Wheels	Painted Steel	19.5", 22.5"; 8, 10 Stud
Tires	Goodyear, Michelin	