



## INTERNATIONAL® 4400 4X2 Mid Cab Tractor

### Product Specifications

Model Configurations	4400 4x2 Mid Cab Tractor			Standard	Maximum
					Front GAW Rear GAW Total GVW

  

Wheelbase (in.)	Chassis Weights (lbs)			Dimensions (in.)				Turning Radius	
	Front	Rear	Total	Back of Cab to Rear Axle	Back of Cab to End of Frame	Center of Rear Axle to End of Frame	Over All Length	To Curb	Bumper Clearance
136	6000	3100	9100	68.9	103.9	35	210.9	19ft. 9in.	20ft. 10in.
144	6022	3122	9144	76.9	111.9	35	218.9	20ft. 9in.	21ft. 10in.
148	6028	3127	9155	80.9	115.9	35	222.9	21ft. 3in.	22ft. 4in.
150	6030	3130	9160	82.9	117.9	35	224.9	21ft. 6in.	22ft. 6in.
156	6039	3139	9178	88.9	123.9	35	230.9	22ft. 2in.	23ft. 3in.

<b>Frame Rails</b>	50,000 PSI 80,000 PSI 120,000 PSI	10.125" 10.250" 10.125"
<b>Front Axle</b>	International	10,000; 12,000 lb Capacity
<b>Front Suspension</b>	Parabolic Taper Leaf w/shocks	10,000; 12,000 lb Capacity
<b>Brakes</b>	Tractor Air Brake System with ABS	
<b>Steering</b>	Ross, Shepard	
<b>Exhaust System</b>	Single, Horizontal w/ Short Tail Pipe or Vertical Muffler, Frame Mounted Right Side	
<b>Electrical System</b>	Leece-Neville Delco-Remy America Inc. International	110, 140, 160 Amp Alternators 100, 110, 135, 145 Amp Alternators 1100, 1300, 1850, 1950, 2775 CCA Battery System



## INTERNATIONAL® 4400 4X2 Mid Cab Tractor

### Product Specifications

	Delphi	1400, 2100 CCA Battery System
	Halogen Headlights	
<b>Front End</b>	Tilting Fiberglass Hood With Three Piece Construction Chrome Grille	
<b>Paint</b>	Base Coat / Clear Coat	
<b>Clutch</b>	Eaton Fuller	
<b>Engine &amp; Equipment</b>	International DT466 High Torque	215 HP/620 lb-ft to 250 HP/800 lb-ft
	International DT530 Standard Torque	275 HP/800 lb-ft to 300 HP/950 lb-ft
	Air Cleaner	Single/Dual Element
<b>Transmissions</b>	Fuller Allison	6, 7, 10 Speed Manual MD Series Close and Wide Ratio 5 and 6 Speed Automatics
<b>Rear Axle (Single)</b>	International	19,000; 21,000; 22,000; 23,000 lb Capacity
<b>Rear Suspension (Single)</b>	International Air Suspension	20,000 lb Capacity w/9.25" Ride Height
	Hendrickson Air Suspension	23,000 lb Capacity w/9.5" Ride Height
	Spring Suspension	20,000; 23,500 lb Capacity Vari-Rate
<b>Fuel Tank</b>	50 – 140 U.S. Gallons Total Capacity	Mounted Under Cab Right, or Right and Left
<b>Cab</b>	Conventional Steel Cab Extended Conventional Steel Cab	107.0" BBC
<b>Interior Trim</b>	Deluxe, Premium	



## INTERNATIONAL® 4400 4X2 Mid Cab Tractor

### Product Specifications

---

<b>Mirrors</b>	(02) Rectangular w/Breakaway Type Brackets	
<b>Driver Seats</b>	A wide variety of seats including:	<ul style="list-style-type: none"><li>• Air-Suspension or Non-Suspension, High Back.</li><li>• Self-Contained w/ Compressor.</li><li>• Full Width w/ Fixed Mid Back.</li></ul>
<b>Passenger Seats</b>	A wide variety of seats including:	<ul style="list-style-type: none"><li>• Two-Man Passenger w/ Storage Compartment</li><li>• Non-Suspension, High Back</li><li>• Air-Suspension, High Back</li></ul>
<b>Front Wheels</b>	Painted Steel, Polished Aluminum	22.5"; 10 Stud
<b>Rear Wheels</b>	Painted Steel, Polished Aluminum	22.5"; 10 Stud
<b>Tires</b>	Goodyear, Michelin, Bridgestone	